

SYNTULA ECO F 0W40

SYNTULA ECO F 0W40 is a fully synthetic engine oil of the latest generation, for the lubrication of gasoline and diesel engines. Due to its very low viscosity, immediate lubrication after starting is obtained, together with a high level of fuel economy.

SYNTULA ECO F 0W40 meets the following specifications:

API SN/ CF
ACEA A3/ B4-10
BMW LONG LIFE 01
MB: Approval 229.5 & 229.3
VW: 502 00
VW: 505 00
RENAULT: RN 0700
RENAULT: RN 0710

APPLICATIONS :

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			0W40
Density at 15°C	D4052	kg/m ³	844
Viscosity at 40°C	D445	cSt	78
Viscosity at 100°C	D445	cSt	13.7
Viscosity at -35°C	D5293	cP	6040
Viscosity index	D2270		178
Flash point COC	D92	°C	220
Pour point	D6892	°C	-57
TBN	D2896	gKOH/kg	10.1

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.

Product code:ARV115