

SYNTULA ECO F 5W30

SYNTULA ECO F 5W30 is a full synthetic lubricant based on carefully selected very high quality base oils, providing outstanding wear and sludge protection, even under the most severe driving conditions. Due to its enhanced frictional properties, improved fuel economy is obtained.

SYNTULA ECO F 5W30 meets the following specifications:

API SN
 CHRYSLER MS6395
 FORD: WSS-M2C946-A
 GM: dexos 1
 ILSAC: GF-5

APPLICATIONS :

This motor oil has been specially designed to meet the latest requirements for most American and Asian passenger cars, SUV's and light vans. Originally intended for fuel-injected gasoline engines, including turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D4052	kg/m ³	856
Viscosity at 40°C	D445	cSt	64.1
Viscosity at 100°C	D445	cSt	10
CCS Viscosity at -30°C	D5293	cP	6300
Viscosity index	D2270		162
Flash point COC	D92	°C	229
Pour point	D6892	°C	-45
TBN	D2896	gKOH/kg	8.1

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical developments.

Product code: ARV135