

ULTIM SPORT 5W40

A universal, ester fortified, synthetic motor oil developed according the most recent technology and based on specially selected base oils with a high natural viscosity index.

With the addition of a well-balanced choice of advanced additives.

PERFORMANCE LEVEL

- ACEA C3-12
- API SN/CF
- VW 502.00/505.00/505.01
- MB 229.31/226.5
- BMW Longlife-04
- Ford M2C917-A
- Porsche A40
- Renault RN0700/RN0710
- Dexos 2
- Fiat 9.55535-S2

FEATURES

- a high and very stable viscosity index
- high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

TYPICAL CHARACTERISTICS:

Test	Method	Unit	Average result
Density at 15°C		kg/l	0,85
Viscosity at -250°C		mPa.s	4469
Viscosity at 40°C	ASTM D 445	mm2/s	92
Viscosity at 100°C	ASTM D 445	mm2/s	15
Viscosity index	ASTM D 2270		183
Pour Point	ASTM D 97	°C	-42
Total Base Number	ASTM D 2896	mgKOH/g	7,4

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Art.:ARV121