

PURE - RACE 24H

FULLY SYNTHETIC RACING MOTOROIL.

A fully synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming



★ APPLICATIONS

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

★ PERFORMANCE LEVEL

- ACEA A3/B4-12
- API SN/CF

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.867
Viscosity 40 °C	mm ² /s	155.10
Viscosity 100 °C	mm ² /s	24.20
Viscosity Index		189
Flash Point COC	°C	238
Pour Point	°C	-48
Total Base Number	mgKOH/g	10.5
Sulphate Ash	%	1.33
Viscosity -25 °C	mPas	6040

★ PACKAGING

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium
T +32 56 72 62 29 - F +32 56 72 67 37 - E info@ardeca-lubricants.be