

Product Data

SYNTH - PRO OW30

FULL SYNTHETIC MOTOR OIL

A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

🖌 APPLICATIONS

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

\star PERFORMANCE LEVEL

- ACEA C3-12
- Meets the requirements of
- VW 504.00/507.00

CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.842
Viscosity 40 °C	mm²/s	64.00
Viscosity 100 °C	mm²/s	12.00
Viscosity Index		178
Flash Point COC	°C	195
Pour Point	°C	51
Total Base Number	mgKOH/g	8.3
Sulphate Ash	%	0.78
Viscosity -35 °C	mPas	5750



Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium T +32 56 72 62 29 - F +32 56 72 67 37 - E <u>info@ardeca-lubricants.be</u>