

Product Data

CERA-MIX 5W40

SYNTHETIC MOTOR OIL INCLUDING CERAMIC BORON ADDITIVE

This 5W40 synthetic ceramic motor oil is a full synthetic lubricant based on carefully selected very high quality base oils. It is formulated with excellent additives to meet the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a Mid SAPS (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms. It provides reliable protection of after-treatment devices and Diesel Particulate Filters. The oil is very universal in use and can be used for petrol and diesel engines.



★ APPLICATIONS

Specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbodiesel engines. The ceramic 5W40 oil is also perfect for the lubrication of the latest generation Petrol cars.

★ PERFORMANCE LEVEL

- ACEA C3-12
- API SN/CF
- BMW LONGLIFE-04
- MB 226.5/229.31/229.51
- GM DEXOS 2
- PORSCHE A40
- RENAULT RN 0700/0710
- VW 502.00/505.00/505 01
- FORD WSS-M2C917-A

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.850
Viscosity -30 °C	mPas	5500
Viscosity 40 °C	mm ² /s	82.80
Viscosity 100 °C	mm ² /s	14.00
Viscosity Index		175
Flash Point COC	°C	232
Pour Point	°C	-42
Total Base Number	mgKOH/g	7.4
Sulphate Ash	%	0.77

★ PACKAGING



12x1L



IBC

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium
T +32 56 72 62 29 - F +32 56 72 67 37 - E info@ardeca-lubricants.be