

Product Data

SYNTH - MS 5W30

SYNTHETIC MOTOR OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils. This high-performance engine oil with low viscosity is specifically developed to provide the highest fuel economy and lowest CO2 emissions.



★ APPLICATIONS

Specifically recommended for Peugeot and Citroën gasoline and diesel engines equipped with diesel particulate filters. Most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

★ PERFORMANCE LEVEL

- ACEA: C2-12
- API: SN/CF
- FIAT: 9.55535-S1
- PSA: Oil meeting specification B71 2290
- RENAULT: RN 0700

★ FEATURES

Aftertreatment protection : full aftertreatment system protection.
Total engine protection : outstanding engine cleanliness and durability.
Fuel economy : lower fuel consumption and CO2 emissions.

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.853
Viscosity -30 °C	mPas	5550
Viscosity 40 °C	mm ² /s	61.70
Viscosity 100 °C	mm ² /s	10.50
Viscosity Index		160
Flash Point COC	°C	236
Pour Point	°C	-45
Total Base Number	mgKOH/g	7.7
Sulphate Ash	%	0.76

★ PACKAGING



12x1L



4x4L



3x5L



20L



60L



210L

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium

T +32 56 72 62 29 - F +32 56 72 67 37 - E info@ardeca-lubricants.be