

Product Data

SYNTH - MS OW30

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the PSA EURO VI Blue HDi DW10F engines with exhaust after treatment and turbocharger. This specification demands high stability to ensure long oil drain intervals. It also addresses the use of biofuels. There is a fuel economy benefit over a 5W40 reference oil of 4,2%.



APPLICATIONS

This product was primarely developed for mandatory use in the PSA EURO VI Blue HDi DW10F engines and particularly ones equiped with e-HDI using Stop & Start technologies. This product is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for todays cars with extended service intervals.

★ PERFORMANCE LEVEL

• ACEA: C2-12

• PSA: B71 2312

• FIAT: 9.55535-GS1

• FIAT: 9.55535-DS1

★ FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

★ CHARACTERISTICS

	unit	average value
	unit	average value
Density at 15 °C	kg/l	0.849
Viscosity 40 °C	mm²/s	55.10
Viscosity 100 °C	mm²/s	9.80
Viscosity Index		160
Pour Point	°C	-51
Total Base Number	mgKOH/g	6.2
Sulphate Ash	%	0.54
Viscosity -35 °C	mPas	5920

★ PACKAGING





20L

210L

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium T +32 56 72 62 29 - F +32 56 72 67 37 - E <u>info@ardeca-lubricants.be</u>