

Product Data

RACING - PLUS 10W60

FULLY SYNTHETIC RACING MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation for the lubrication of all gasoline and diesel engines with turbo.



★ APPLICATIONS

4 stroke gasoline engines, multi-valves, turbo. 4 stroke diesel engines, with or without turbo.

★ PERFORMANCE LEVEL

- ACEA: A3/B4-08
- API: SN/CF
- BMW: LONGLIFE-01
- BMW: M-MODELS
- MB: 229.3
- VW: 501 01
- VW: 505 00

★ FEATURES

Cold start : very good fluidity at low temperature.

Total engine protection : outstanding engine cleanliness and durability.

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.854
Viscosity 40 °C	mm ² /s	163.30
Viscosity 100 °C	mm ² /s	23.30
Viscosity Index		173
Flash Point COC	°C	224
Pour Point	°C	-40
Total Base Number	mgKOH/g	10.5
Sulphate Ash	%	1.33
Viscosity -25 °C	mPas	6190

★ PACKAGING



12x1L



4x4L



3x5L



20L



60L



210L

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium

T +32 56 72 62 29 - F +32 56 72 67 37 - E info@ardeca-lubricants.be