Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking Product identifier · Trade name: RACING+ 10W60 Article number: ARD010015 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 Consumer uses: Private households / general public / consumers Product category PC24 Lubricants, greases, release products Process category PROC2 Use in closed, continuous process with occasional controlled exposure PROC8a Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at non-dedicated facilities Transfer of substance or preparation (charging/discharging) from /to vessels/large PROC8b containers at dedicated facilities PROC20 Heat and pressure transfer fluids in dispersive, professional use but closed systems PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing) · Environmental release category ERC9a Wide dispersive indoor use of substances in closed systems ERC9b Wide dispersive outdoor use of substances in closed systems ERC4 Industrial use of processing aids in processes and products, not becoming part of articles Industrial use of substances in closed systems ERC7 Application of the substance / the mixture Engine oil · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Vroman NV Oudenaardestraat 49 8570 Vichte info@ardeca-lubricants.be 0032 56 72 62 29 Further information obtainable from: Product safety department - 0032 56 72 62 29. 1.4 Emergency telephone number: 0032 56 72 62 29 (9 AM to 4 PM, Monday to Friday) National Poison Information Centre (NVIC): Tel. nr. +31 30 - 2748888 - Only for the purpose of informing medical personnel in case of acute intoxications. **SECTION 2: Hazards identification** 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.

· Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008 Void ·

Hazard pictograms Void

Signal word Void

· Hazard statements Void

(Contd. on page 2)

Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

(Contd. of page 1)

Trade name: RACING+ 10W60

· Additional information:

EUH208 Contains Calcium long chain alkarylsulphonate. May produce an allergic reaction. EUH210 Safety data sheet available on request.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions. ·

Dangerous components:				
Polymer	Polyolefin polyamine succinimide, Polyol R53 Aquatic Chronic 4, H413	2.5-10%		
CAS: 68649-42-3 EINECS: 272-028-3	zinc-alkyl-dithiophosphate Xi R41; N R51/53 Eye Dam. 1, H318; Aquatic Chronic 2, H411	1-2.5%		
CAS: 90480-91-4 EINECS: 291-829-9 Reg.nr.: 01-2119524004-56	HOB calcium branched chain alkyl phenate sulphide R53 Aquatic Chronic 4, H413	1-2.5%		
Polymer	Branched alkylphenol and Calcium branched alkylphenol T Repr. Cat. 2 R60; Xi R36/38; N R50/53 Repr. 1B, H360; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-1.0%		

Additional information:

The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346. For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed If

swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, dry chemical, or foam. Water can be used to cool and protect exposed material.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

(Contd. on page 3)

GB

Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

Trade name: RACING+ 10W60

Wear fully protective suit.

(Contd. of page 2)

GB

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. \cdot 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Remove from the water surface (e.g. skim or suck off).
- 6.4 Reference to other sections
- No dangerous substances are released.
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special measures required. Avoid the formation of oil haze.

Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities ·

Storage:

• Requirements to be met by storerooms and receptacles: Store only in the original receptacle. • Information about storage in one common storage facility: Not required.

- · Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7. · 8.1

Control parameters

- · Ingredients with limit values that require monitoring at the workplace:
- Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.
- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work. ·

Respiratory protection: Not required.

Protection of hands:



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves • Material of gloves Nitrile rubber, NBR

PVC gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore (Contd. on page 4)

Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

(Contd. of page 3)

Trade name: RACING+ 10W60

to be checked prior to the application. • Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 \cdot Eye protection: Goggles recommended during refilling \cdot

Body protection: Protective work clothing

SECTION 9: Physical and chemical	properties			
 9.1 Information on basic physical and chemical properties General Information Appearance: 				
Form:	Liquid			
Colour:	Brown			
· Odour:	Characteristic			
 Change in condition Melting point/Melting range: Boiling point/Boiling range: Drip point: 	Undetermined. Undetermined.			
Pour point	-40 ℃ (ASTM D97)			
 Flash point: Flammability (solid, gaseous): Self-igniting: Danger of explosion: Explosion limits: Lower: 	 > 110 ℃ Not applicable. Product is not selfigniting. Product does not present an explosion hazard. Not determined. 			
Upper:	Not determined.			
Density at 20 °C:	0.853 g/cm ³			
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.			
Partition coefficient (n-octanol/water): Not determined.				
· Viscosity: 40 ℃	163 mm²/s (ASTM D445)			
 Solvent content: Organic solvents: 9.2 Other information 	0.0 % No further relevant information available.			

SECTION 10: Stability and reactivity

10.1 Reactivity

0.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: To

avoid thermal decomposition do not overheat.

 \cdot 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents. \cdot 10.4

Conditions to avoid No further relevant information available.

(Contd. on page 5)

GB 📕

Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

(Contd. of page 4)

Trade name: RACING+ 10W60

- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- \cdot on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

- · Sensitisation For respiratory and skin sensitisation: Not expected to be a sensitiser.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available. ·
- Other information: The product is difficultly biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue
 - 13 02 06* synthetic engine, gear and lubricating oils

(Contd. on page 6)

Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

Trade name: RACING+ 10W60

(Contd. of page 5)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR,ADN, ADN, IMDG, IATA	Void
 14.2 UN proper shipping name ADR,ADN, ADN, IMDG, IATA 	Void
• 14.3 Transport hazard class(es)	
· ADR,ADN, ADN, IMDG, IATA · Class	Void
 14.4 Packing group ADR,ADN, IMDG, IATA 	Void
 14.5 Environmental hazards: Marine pollutant: 	No
14.6 Special precautions for user	Not applicable.
 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
· UN "Model Regulation":	-

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This information is based on our present knowledge. However, this shall not constitute a guarantee for

any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H360 May damage fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

R36/38 Irritating to eyes and skin.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

.

.

- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R53 May cause long-term adverse effects in the aquatic environment.

(Contd. on page 7)

Printing date 26.05.2015

Version number 1

Revision: 12.01.2015

Trade name: RACING+ 10W60

DCO Marcine air fastilite	(Contd. of page 6)		
R60 May impair fertility.			
Department issuing MSDS: Product safety department.			
Contact: Product safety department			
Abbreviations and acronyms:			
RID: Règlement international concernant le transport des marchandises dangereuses par chem Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation	in de fer (Regulations		
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agre International Carriage of Dangerous Goods by Road)	eement concerning the		
IMDG: International Maritime Code for Dangerous Goods			
IATA: International Air Transport Association			
GHS: Globally Harmonised System of Classification and Labelling of Chemicals			
EINECS: European Inventory of Existing Commercial Chemical Substances			
ELINCS: European List of Notified Chemical Substances			
CAS: Chemical Abstracts Service (division of the American Chemical Society)			
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2			
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye			
Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Repr. 1B:			
Reproductive toxicity, Hazard Category 1B			
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1			
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1			
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4			
Sources EC/453-2010			
	GB		