

RACING - PLUS 5W50

FULLY SYNTHETIC RACING MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils with a high viscosity index for the lubrication of gasoline and diesel engines with turbocharging. This oil is distinguished by an excellent fluidity at low temperature, which allows a perfect cold start, along with a high viscosity at hot engine.



★ APPLICATIONS

This oil is used in 4-stroke gasoline engines, multi valves, and 4-stroke diesel engines with or without turbo. It is specifically suitable for sporty driving conditions.

★ PERFORMANCE LEVEL

- ACEA: A3/B4-12
- API: SN/CF
- BMW: LONGLIFE-01
- PORSCHE A40
- MB: 229.3
- VW: 500 00
- VW: 505 00

★ FEATURES

Total engine protection : performance in keeping the engine clean.

Cold start : excellent fluidity at low temperature.

Driving style : sporty driving.

★ CHARACTERISTICS

| | unit | average value |
|-------------------|--------------------|---------------|
| Density at 15 °C | kg/l | 0.853 |
| Viscosity -30 °C | mPas | 4670 |
| Viscosity 40 °C | mm ² /s | 100.90 |
| Viscosity 100 °C | mm ² /s | 17.30 |
| Viscosity Index | | 188 |
| Flash Point COC | °C | 223 |
| Pour Point | °C | -39 |
| Total Base Number | mgKOH/g | 10.5 |
| Sulphate Ash | % | 1.33 |

★ PACKAGING



12x1L



4x4L



3x5L



20L



60L



210L

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium

T +32 56 72 62 29 - F +32 56 72 67 37 - E info@ardeca-lubricants.be