

Product Data

SYNTH - SX 5W40

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils and high quality additives of the latest generation, specially designed to meet the strict requirements of manufacturers. This provides an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.



★ APPLICATIONS

This oil is used in gasoline engines of cars, which demand the highest performance and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

★ PERFORMANCE LEVEL

- ACEA: A3/B4-12
- API: SN/CF
- BMW: LONGLIFE-01
- MB: 226.5
- MB: 229.3
- OPEL: GM-LL-B-025
- Fiat 9.55535-M2
- PORSCHE: A40
- PSA: B71 2296
- RENAULT: RN 0700
- RENAULT: RN 0710
- VW: 502 00
- VW: 505 00

★ FEATURES

Total engine protection : performance in keeping the engine clean.

Cold start : excellent fluidity at low temperature.

Drain interval extension : longer oil drain interval.

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.853
Viscosity -30 °C	mPas	5740
Viscosity 40 °C	mm ² /s	90.2
Viscosity 100 °C	mm ² /s	15
Viscosity Index		175
Flash Point COC	°C	223
Pour Point	°C	-42
Total Base Number	mgKOH/g	10.5
Sulphate Ash	%	1.33

★ PACKAGING



12x1L



4x4L



3x5L



20L



60L



210L

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium

T +32 56 72 62 29 - F +32 56 72 67 37 - E info@ardeca-lubricants.be