

## Product Data

# SYNTH - C4 5W30

## SYNTHETIC MOTOR OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.



## ★ APPLICATIONS

Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).

## ★ PERFORMANCE LEVEL

- ACEA: C3-12, C4-12
- MB: 229.51/226.51
- RENAULT: RN 0720

## ★ FEATURES

Aftertreatment protection : full aftertreatment system protection.

Total engine protection : outstanding engine cleanliness and durability.

Fuel economy : lower fuel consumption and CO2 emissions.

## ★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.851
Viscosity -30 °C	mPas	6020
Viscosity 40 °C	mm <sup>2</sup> /s	66.00
Viscosity 100 °C	mm <sup>2</sup> /s	12.10
Viscosity Index		174
Flash Point COC	°C	228
Pour Point	°C	-39
Total Base Number	mgKOH/g	7.3
Sulphate Ash	%	0.49

## ★ PACKAGING



12x1L



4x4L



3x5L



20L



60L



210L

30L

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium

T +32 56 72 62 29 - F +32 56 72 67 37 - E [info@ardeca-lubricants.be](mailto:info@ardeca-lubricants.be)