



L'huile des records du monde

GALAXIE - SAE 5W-40

100% synthetic racing oil

APPLICATIONS

This ESTER based 100% synthetic lubricant is designed to ensure optimal engine lubrication under extreme service conditions. Specially developed to meet the requirement of GT or sports gasoline engines used on road or circuits

MAIN PHYSICAL DATA

		Units	5W-40
Density at	20° C	kg/m ³	857
Kinematic viscosity at	40° C	mm ² /s	91
Kinematic viscosity at	100° C	mm ² /s	15
Viscosity index			174
Pour point		° C	- 39
Flash point Cleveland open cup		°C	216
Dynamic viscosity at	- 30°C	mPa.s	6100

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- SAE 5W40 viscosity provides excellent performance at start-up whilst offering outstanding engine protection at very high temperatures for maximum oil pressure stability under any service conditions.
- **Excellent shear resistance ensuring a continuous lubrication** at hot temperature even under severe service conditions
- **Reinforced thermal stability** prevents the formation of deposits
- Very low volatility for reduced oil consumption
- Outstanding detergent-dispersant properties keeping the engine clean

SPECIFICATIONS

API SL; ACEA A3/B3

This range is available in 6 viscosities to meet the service conditions of each type of competition, engines and settings: SAE 0W-40, SAE 5W30, SAE 5W-40, SAE 5W-50, SAE 15W-50 & SAE 10W-60.

For an optimal oil pressure, select this product or one from YACCO GALAXIE range according to the service condition and the importance of unburned fuel dilution level.