



Gulf Formula Elite

Premium Catalyst Compatible Passenger Car Motor Oil

Product Description

Gulf Formula Elite is a supreme performance fully synthetic catalyst compatible passenger car motor oil capable of providing fuel economy benefit. It is formulated from finest quality synthetic base stocks and latest additive technology meeting mid SAPS (Sulphated Ash, Phosphorous & Sulphur) requirements. It is designed to provide the protection against Low Speed Pre-Ignition (LSPI) and timing chain wear issues generally observed in latest turbocharged Gasoline Direct Injection (GDI) engines. It also provides extended life & maintains efficiency of the after treatment devices of all modern gasoline and diesel light duty vehicles. Recommended for passenger car, SUV, light van and truck applications requiring ACEA C3 quality oils.

Features & Benefits

- The special formula helps in protecting the engines from Low Speed Pre-Ignition (LSPI) and Timing chain wear issues observed in latest turbocharged Gasoline Direct Injection (GDI) engines
- Active cleaning agents reduces piston deposits and sludge build-up facilitating extended engine life
- Low ash content reduces particulate build-up in diesel particulate filters
- Outstanding thermo-oxidative stability reduces oil degradation and enables extended drain intervals
- Unique additive chemistry helps minimise soot related oil thickening and wear
- Latest mid SAPS additive technology minimises poisoning of TWC (Three Way Catalyst) and prolongs life of after treatment devices
- Excellent low temperature fluidity aids cold start and protects against wear at start-up

Applications

- All gasoline and diesel engines meeting Euro 6 & Euro 5 emission norms & requiring mid SAPS oils meeting ACEA C3 performance level
- Modern passenger cars, SUVs, light vans & trucks powered by gasoline or diesel engines
- Suitable for high performance and high powered vehicles requiring such type of oils

Specifications, Approvals & Typical Properties

Meets the following Specifications		0W-40	5W-30	5W-40
ACEA C3		X	X	X
Renault RN0700/ 0710		X	X	X
MB 229.31, OPEL OV0401547			X	X
Has the following Approvals				
API SP, API SN Plus MB-Approval 229.51, MB-Approval 229.52		X	X	X
BMW Longlife-04			X	X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	13.4	11.9	13.2
Viscosity Index	D 2270	212	195	204
Flash Point, °C	D 92	235	230	232
Pour Point, °C	D 97	-48	-42	-42
TBN, mg KOH/g	D 2896	9.5	9.3	9.6
Density @ 15°C, Kg/l	D 1298	0.845	0.852	0.852
Sulphated Ash, %wt	D 874	0.77	0.77	0.79
Phosphorus, %wt	D 4047/ICP	0.077	0.077	0.074
Sulphur, %wt	D 129	0.21	0.19	0.19

April 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.