



Shell Helix Ultra *ECT MULTI* 5W-30

Fully synthetic motor oil - Shell's ultimate protection for vehicle emission systems

Shell Helix Ultra ECT MULTI 5W-30 features its most advanced emissions-compatible technology that helps to keep diesel particulate filters clean to help maintain engine performance. It meets the requirements from multi leading OEMs.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- **Approved by car manufacturers**
Approved for use by the makers of high-performance vehicles.
- **Multi-fuel capability**
Can be used for gasoline, diesel and gas engines, and is also suitable for biodiesel and gasoline/ethanol blends.

- BMW LongLife-04
- MB-Approval 229.51
- VW Standard 504.00, 507.00

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at:
<http://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Specifications, Approvals & Recommendations

- ACEA C3
- API SN

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra ECT MULTI 5W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	11.8
Kinematic Viscosity	@40°C	cSt	ASTM D445	66.8
Viscosity Index			ASTM D2270	174
Density	@15°C	kg/m ³	ASTM D4052	836
Flash Point		°C	ASTM D92	234
Pour Point		°C	ASTM D97	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Helix Ultra ECT Multi 5W-30 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.