## **BIZOL Allround 20W-50**



Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

2016-01-06

1/2



**BIZOL Allround 20W-50** is a high-performance multigrade motor oilfor petrol and diesel engines. It is universal in its application, among others also suitable for a commercial vehicle fleet. Designed specially for high-load engines. It meets the requirements of most leading vehicle and engine manufacturers.

## **BENEFITS**

- universal use of petrol and diesel engines with or without exhaust-gas-turbocharger and with or without charge air cooler
- extremely low evaporation loss
- · high resistance to shearing strain and ageing

**SPECIFICATIONS** 

ACEA A3 / B4 / E3

MIL L 2104 E

API CG-4 / SL

APPROVALS /
RECOMMENDATIONS

ALLISON C4

CATERPILLAR TO-2

**MAN** 271

**MERCEDES BENZ** MB 228.3 / 229.1

VOLVO VDS

## **TECHNICAL DATA**

Characteristics	Measurements	Method
Flash Point (Cleveland)	225 °C	DIN ISO 2592
Viscosity at 100°C	18,9 mm <sup>2</sup> /s	DIN 51 562
Viscosity class SAE	20W-50	
TBN (Total base number)	11 mg KOH/g	DIN ISO 3771
Evaporation loss	7,5 %	
Viscosity at 40°C	150 mm²/s	DIN 51 562
Viscosity index	144	DIN ISO 2909
Pour Point	-21 °C	DIN ISO 3016
Colour	4,5	DIN ISO 2049
Appearance	brown, clear	

## **BIZOL Allround 20W-50**



Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

2016-01-06

2/2

TE	CH	MI	CA	A II	D	ΔΤ	Δ
	$\sim$ 111	1 1 1			-		$\overline{}$

Characteristics	Measurements	Method
Density at 15 °C	0,878 g/cm³	DIN 51 757
Oxide ashes	1,4 %	DIN 51575

AVAILABLE PACK SIZE, ARTICLE

1L	ART. 82110
4L	ART. 82116
5L	ART. 82111
20L	ART. 82112
60L	ART. 82113
200L	ART. 82114

**INSTRUCTIONS** 

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.