

BIZOL Allround

**EXCELLENT ENGINE CLEANING
FORMULA FOR EVERY DRIVER**



BIZOL Allround 15W-40 is a modern high-performance Mineral Motor Oil for all year-round use in petrol and diesel engines, including engines with turbocharger and catalytic converter. Due to the combination of advanced additives of the latest generation it ensures excellent protection against oxidation, wear, improved protection against foaming, and has anti-corrosive and purifying properties.

BENEFITS

- suitable for compatibility with catalytic converters
- outstanding for use as a year-round oil
- especially developed for mixed fleets

SPECIFICATIONS

ACEA A3 / B3 / E2

API SJ / CF-4

APPROVALS / RECOMMENDATIONS

ALLISON

C4

AUDI/VW/SEAT/SKODA

VW 501 01 / 505 00

CATERPILLAR

TO-2

MAN

271

MERCEDES BENZ

MB 228.1 / 229.1

MTU

Type 1

VALTRA

E

VOLVO

VDS

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	220 °C	DIN ISO 2592
Viscosity at 100°C	13 mm²/s	DIN 51 562
Density at 15 °C	870 kg/m³	DIN 51 757
Viscosity class SAE	15W-40	
TBN (Total base number)	8 mg KOH/g	
Viscosity at 40°C	90 mm²/s	DIN 51 562

TECHNICAL DATA

Characteristics	Measurements	Method
Viscosity index	145	DIN ISO 2909
Pour Point	-28 °C	DIN ISO 3016
Sulfate ashes	1 %	DIN 51575

AVAILABLE PACK
SIZE, ARTICLE

1L	ART. 82010
4L	ART. 82016
5L	ART. 82011
20L	ART. 82012
60L	ART. 82013
200L	ART. 82014

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.