

## BIZOL Allround

**EXCELLENT ENGINE CLEANING  
FORMULA FOR EVERY DRIVER**



**BIZOL Allround 10W-40** is a high-performance, low friction motor oil manufactured using the latest additive technology and synthetic components. It is suitable for all year-round use in passenger cars with petrol and diesel engines with or without exhaust-gas turbochargers and charge-air coolers. Also suitable for LPG/CNG engines according to the manufacturer's instructions.

## BENEFITS

- optimum engine cleanliness
- high resistance to ageing
- high lubrication reliability at high and low temperatures

## SPECIFICATIONS

ACEA A3 / B4

JASO MA

API SN / CF

## APPROVALS / RECOMMENDATIONS

**AUDI/VW/SEAT/SKODA**

VW 502 00 / 505 00

**MERCEDES BENZ**

MB 229.1

**PEUGEOT/CITROËN**

PSA B71 2294

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	220 °C	DIN ISO 2592
Viscosity at 100°C	13 mm <sup>2</sup> /s	DIN 51 562
Density at 15 °C	870 kg/m <sup>3</sup>	DIN 51 757
Viscosity class SAE	10W-40	
Evaporation loss	9,2 %	
Viscosity at 40°C	88 mm <sup>2</sup> /s	DIN 51 562
Viscosity index	147	DIN ISO 2909
Pour Point	-36 °C	DIN ISO 3016
Colour	3,5	DIN ISO 2049
Sulfate ashes	1,2 %	DIN 51575
TBN	9 mgKOH/g	DIN ISO 3771

## AVAILABLE PACK SIZE, ARTICLE

1L	ART. 83010
4L	ART. 83016
5L	ART. 83011
20L	ART. 83012
60L	ART. 83013
200L	ART. 83014

## INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.