

## BIZOL Allround

**EXCELLENT ENGINE CLEANING  
FORMULA FOR EVERY DRIVER**



**BIZOL Allround 5W-30** is a modern low-friction motor oil of the highest quality suitable for year-round use. A combination of unconventional base oils made on the basis of synthesis technology with the additive package of the latest generation (mid SAPS technology) guarantees a motor oil with low viscosity and high stability against shearing. It reliably prevents deposits, reduces engine friction, and protects against wear. As a result fuel economy and time extended service life of the engine are preserved. This product is recommended for all petrol and diesel engines including turbochargers and catalytic converters. Especially recommended for petrol engines with TWC and for diesel engines with DPF.

## BENEFITS

- reduced exhaust emissions
- optimal wear protection and extended service life of the engine is possible
- optimum oil and fuel savings

## SPECIFICATIONS

ACEA C3

API SN / CF

## APPROVALS / RECOMMENDATIONS

**AUDI/VW/SEAT/SKODA**

VW 502 00 / 505 00 / 505 01

**BMW**

LL-04

**FIAT**

9.55535 S2

**FORD**

WSS-M2C-917-A

**GENERAL MOTORS/OPEL**

DEXOS 2

**MERCEDES BENZ**

MB 229.52

MB 229.51

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	220 °C	DIN ISO 2592
Viscosity at 100°C	11,5 mm²/s	DIN 51 562
Density at 15 °C	860 kg/m³	DIN 51 757
Viscosity class SAE	5W-30	DIN 3771
TBN (Total base number)	8,5 mg KOH/g	
Viscosity at 40°C	65 mm²/s	DIN 51 562
Viscosity index	170	DIN ISO 2909

## TECHNICAL DATA

Characteristics	Measurements	Method
Pour Point	-36 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	3,5 mPas	
Colour	3	DIN ISO 2049
Sulfate ashes	0,8 %	DIN 51575

## AVAILABLE PACK SIZE, ARTICLE

1L	ART. 85110
4L	ART. 85116
20L	ART. 85112
60L	ART. 85113
200L	ART. 85114

## INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.