## **BIZOL Green Oil 10W-40**



2016-10-06

1/2

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com



**BIZOL Green Oil 10W-40** guarantees the highest oil stability for the whole life cycle of the engine. It is especially suitable for engines working under heavy city traffic conditions. Its excellent corrosion protection and lubri cation properties remainunchanged even under extreme operating conditions. The green colour of this product is an indicator of its incomparable technology and unique additives. This innovative motor oil has a very high anti-wear protection quality. It was developed by German engineers as a universal motor oil for both old and new diesel and petrol engines.

BENEFITS	<ul> <li>smooth engine running especially in urban traffic</li> <li>saves petrol and reduces pollutant emission</li> <li>very good wear-protection</li> </ul>				
SPECIFICATIONS	ACEA A3 / B4	API SN / CF			
APPROVALS / RECOMMENDATIONS	AUDI/VW/SEAT/SKODA MERCEDES BENZ PEUGEOT/CITROËN RENAULT	VW 501 01 / 505 00 MB 229.1 PSA B71 2296 RN 0700 / 0710			
TECHNICAL DATA	Characteristics Flash Point (Cleveland) Viscosity at 100°C Viscosity class SAE ASTM colour number Viscosity at 40°C Viscosity index Viscosity at -25°C Appearance Density at 15 °C	Measurements           220 °C           13,8 mm²/s           10W-40           >8,0           88 mm²/s           161           5000 mPAs           Green           0,865 g/cm³	Method           DIN ISO 2592           DIN 51 562           ASTMD 1500           DIN 51 562           DIN ISO 2909           DIN 51 562           DIN 51 562		

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

TECHNICAL DATA	Characteristics		Measurements	Method
	Sulfate ashes		1,5 %	DIN 51575
	TBN		12 mgKOH/g	DIN ISO 3771
AVAILABLE PACK	1L	ART. 81020		
SIZE, ARTICLE	4L	ART. 81026		
INSTRUCTIONS	On refilling and changing the Engine Oil please follow the operating instructions of			

the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.



2016-10-06

2/2