

## BIZOL Green Oil

**IMPROVES PERSONAL SAFETY  
IN CITY TRAFFIC**



**BIZOL Green Oil 5W-30** is a highly modern low-friction motor oil for year-round use. It is specially designed for vehicles used permanently in city traffic. The specially developed additives provide **BIZOL Green Oil 5W-30** with its characteristic green colour providing high stability for the engine throughout its entire life cycle. Excellent wear resistance and perfect lubrication characteristics are enhanced under any operating conditions, especially in city traffic.

### BENEFITS

- optimum oil and fuel savings
- very stable lubrication film
- excellent wear resistance especially in the city traffic

### SPECIFICATIONS

ACEA A3 / B4

API SN / CF

### APPROVALS / RECOMMENDATIONS

**AUDI/VW/SEAT/SKODA**

VW 502 00 / 505 00

**BMW**

LL-01

**GENERAL MOTORS/OPEL**

GM LL A-025 / LL B-025

**MERCEDES BENZ**

MB 229.3 / 229.5

**RENAULT**

RN 0700 / 0710

### TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	210 °C	DIN ISO 2592
Viscosity at 100°C	11,5 mm²/s	DIN 51 562
Viscosity at -30°C	4200 mPas	DIN 51 562
Viscosity class SAE	5W-30	
ASTM colour number	>8,0	ASTMD 1500
Viscosity at 40°C	63 mm²/s	DIN 51 562
Viscosity index	176	DIN ISO 2909
Pour Point	-42 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	3,6 mPas	
Colour	green	

TECHNICAL DATA

Characteristics	Measurements	Method
Evaporation loss	7,9 %	
Density at 15 °C	0,860 g/cm³	DIN 51 757
Sulfate ashes	1,3 %	DIN 51575:
TBN	12 mgKOH/g	DIN ISO 3771

AVAILABLE PACK  
SIZE, ARTICLE

1L	ART. 81050
4L	ART. 81056

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.