

## BIZOL Protect

### BEST ENGINE PROTECTION FOR AN EXTENDED ENGINE LIFE



**BIZOL Protect 5W-50** is a modern fully synthetic, low-viscous motor oil for year-round use. The combination of unconventional synthetic base oils with advanced additive technology guarantees a low-viscous, highly shear-resistant motor oil that prevents deposit build-up, reduces engine friction and provides optimum wear protection. It leads to fuel economy and an extended life cycle of the engine.

## BENEFITS

- highest lubrication reliability at high and low temperatures
- optimum oil pressure at all engine speeds
- optimum oil and fuel savings

## SPECIFICATIONS

ACEA A3 / B3

API SL / CF

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	220 °C	DIN ISO 2592
Viscosity at 100°C	18 mm <sup>2</sup> /s	DIN 51 562
Density at 15 °C	850 kg/m <sup>3</sup>	DIN 51 757
Viscosity class SAE	5W-50	
TBN (Total base number)	9 mg KOH/g	DIN ISO 3771
Evaporation loss	7,5 %	
Viscosity at 40°C	115 mm <sup>2</sup> /s	DIN 51 562
Viscosity index	175	DIN ISO 2909
Pour Point	-33 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	>3,5 mPas	
Colour	3,5	DIN ISO 2049
Sulfate ashes	1 %	DIN 51575

## AVAILABLE PACK SIZE, ARTICLE

1L	ART. 85710
4L	ART. 85716
60L	ART. 85713

## INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.