

## BIZOL Protect

### BEST ENGINE PROTECTION FOR AN EXTENDED ENGINE LIFE



**BIZOL Protect 5W-40** is a modern high-performance, low-friction motor oil designed for diesel and petrol engines with or without exhaust-gas turbochargers and charge-air coolers. A modern additive technology in combination with unique base oils provides this product with its outstanding characteristics with respect to reduced friction and wear protection. Thus, it significantly helps to extend the oil change intervals.

## BENEFITS

- suitable for catalytic converters and turbo-chargers
- very good wear-protection
- optimum lubrication even under extreme conditions

## SPECIFICATIONS

ACEA A3 / B4

API SN / CF

## APPROVALS / RECOMMENDATIONS

**AUDI/VW/SEAT/SKODA**

VW 502 00 / 505 00

**BMW**

LL-01

**FIAT**

9.55535 N2

**GENERAL MOTORS/OPEL**

GM LL B-025

**MERCEDES BENZ**

MB 229.3 / 229.1

**PEUGEOT/CITROËN**

PSA B71 2296

**PORSCHE**

A40

**RENAULT**

RN 0700 / 0710

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	224 °C	DIN ISO 2592
Viscosity at 100°C	14 mm²/s	DIN 51 562
Density at 15 °C	860 kg/m³	DIN 51 757
Viscosity class SAE	5W-40	
TBN (Total base number)	10,8 mg KOH/g	
Evaporation loss	11 %	
Viscosity at 40°C	84 mm²/s	DIN 51 562
Viscosity index	174	DIN ISO 2909

TECHNICAL DATA

Characteristics	Measurements	Method
Pour Point	-33 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	3,9 mPas	
Colour	4	DIN ISO 2049
Sulfate ashes	0,9 %	DIN 51575

AVAILABLE PACK  
SIZE, ARTICLE

1L	ART. 85210
4L	ART. 85216
5L	ART. 85211
20L	ART. 85212
60L	ART. 85213
200L	ART. 85214

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.