

## BIZOL Protect

### BEST ENGINE PROTECTION FOR AN EXTENDED ENGINE LIFE



**BIZOL Protect 0W-40** is a highly modern fully synthetic, low-friction motor oil for year-round use. The combination of unique synthetic base oils with advanced additive technology results in an motor oil with low viscosity and high stability. It reliably prevents deposits, reduces friction losses in the engine, and protects from wear. **BIZOL Protect 0W-40** is recommended for use in petrol and diesel engines including those with turbochargers and catalytic converters.

## BENEFITS

- optimal increase of engine service life
- optimum oil and fuel savings
- reduced exhaust emissions

## SPECIFICATIONS

ACEA A3 / B4

API SN / CF

## APPROVALS / RECOMMENDATIONS

**AUDI/VW/SEAT/SKODA**

VW 502 00 / 505 00

**BMW**

LL-01

**MERCEDES BENZ**

MB 229.5 / 229.3

**PORSCHE**

A40

**RENAULT**

RN 0700 / 0710

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	222 °C	DIN ISO 2592
Viscosity at 100°C	13,3 mm²/s	DIN 51 562
Viscosity class SAE	0W-40	
TBN (Total base number)	10,2 mg KOH/g	DIN ISO 3771
Evaporation loss	8,5 %	
Viscosity at 40°C	74,8 mm²/s	DIN 51 562
Viscosity index	182	DIN ISO 2909
Pour Point	-42 °C	DIN ISO 3016
Viscosity at -35°C	5400 mPas	DIN 51 562
High Shear / High Temperature Viscosity	3,7 mPas	

TECHNICAL DATA

Characteristics	Measurements	Method
Density at 15 °C	0,845 g/cm³	DIN 51 757
Sulfate ashes	1 %	DIN 51575

AVAILABLE PACK  
SIZE, ARTICLE

1L	ART. 85510
4L	ART. 85516
20L	ART. 85512
60L	ART. 85513
200L	ART. 85514

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.