

BIZOL Technology

OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



BIZOL Technology 10W-60 is a fully synthetic, high-performance motor oil. It is a modern motor oil specifically designed for four-stroke engines under extreme load. The combination of synthetic base oils and progressive additive technology guarantees an outstanding motor oil that provides excellent protection for the engine against wear. The synthetic components give it an extremely high quality level that is particularly useful for engines that are exposed to high thermal stress.

BENEFITS

- developed for year round use
- optimum lubrication even under extreme conditions
- especially developed for racing and ideally suited for motorcycles

SPECIFICATIONS

API SL / CF

JASO MA-2

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	230 °C	DIN ISO 2592
Viscosity at 100°C	23 mm²/s	DIN 51 562
Viscosity class SAE	10W-60	
ASTM colour number	5,0	DIN ISO 2049
TBN (Total base number)	8,2 mg KOH/g	DIN ISO 3771
Evaporation loss	5,2 %	
Viscosity at 40°C	164 mm²/s	DIN 51 562
Viscosity index	162	DIN ISO 2909
Pour Point	-39 °C	DIN ISO 3016
Density at 15 °C	0,862 g/cm³	DIN 51 757
Sulfate ashes	0,9 %	DIN 51575

AVAILABLE PACK SIZE, ARTICLE

1L	ART. 89310
4L	ART. 89316
20L	ART. 89312
60L	ART. 89313
200L	ART. 89314

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.