

BIZOL Technology

OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



BIZOL Technology 5W-40 is one of the most modern low viscosity all-year motor oils that can be used in diesel and petrol engines with or without exhaust-gas turbochargers and charge-air cooler. Thanks to its state-of-the art HC-Technology and the superior additive package used, this oil provides reduced fuel consumption, remarkable engine performance with extended service intervals. This oil ensures best wear protection and a smooth cold start.

BENEFITS

- prevents desposit build-up
- good friction characteristics
- reduced exhaust emissions

SPECIFICATIONS

ACEA A3 / B4

API SN / CF

APPROVALS / RECOMMENDATIONS

AUDI/VW/SEAT/SKODA

VW 502 00 / 505 00

BMW

LL-01

GENERAL MOTORS/OPEL

GM LL B-025

MERCEDES BENZ

MB 229.5

PORSCHE

A40

RENAULT

RN 0700 / 0710

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	225 °C	DIN ISO 2592
Viscosity at 100°C	14 mm²/s	DIN 51 562
Viscosity at -30°C	3850 mPas	DIN 51 562
Viscosity class SAE	5W-40	
TBN (Total base number)	9,7 mg KOH/g	DIN ISO 3771
Evaporation loss	9 %	
Viscosity at 40°C	83 mm²/s	DIN 51 562
Viscosity index	176	DIN ISO 2909
Pour Point	-33 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	4 mPas	

TECHNICAL DATA

Characteristics	Measurements	Method
Colour	4	DIN ISO 2049
Density at 15 °C	0,857 g/cm³	DIN 51 757
Sulfate ashes	1,2 %	DIN 51575

AVAILABLE PACK
SIZE, ARTICLE

1L	ART. 84610
4L	ART. 84616
20L	ART. 84612
60L	ART. 84613
200L	ART. 84614

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.