BIZOL Technology 5W-30 C4



Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

2016-01-06

1/1



BIZOL Technology 5W-30 C4 is a high-grade motor oil based on the most recent low SAPS technology, which has been especially tailored to suit the requirements of modern final exhaust gas treatment systems. It has been specifically developed for Renault's latest generation of diesel engine cars. It therefore ensures maximum service life of the diesel particle filter, as well as low wear, clean engine operation and long oil change intervals.

BENEFITS

- develped specially for most cars with PSA engines
- optimum protection of the diesel particulate filter against deposits
- increased oil change intervals are possible

SPECIFICATIONS ACEA C1 / C4

APPROVALS /
RECOMMENDATIONS

RENAULT

MERCEDES BENZ

MB 226.51

RN 0720

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	>210 °C	DIN ISO 2592
Viscosity at 100°C	10,9 mm²/s	DIN 51 562
Density at 15 °C	855 kg/m³	DIN 51 757
Viscosity class SAE	5W-30	
Viscosity at 40°C	65 mm²/s	DIN 51 562
Viscosity index	>170	DIN ISO 2909
Pour Point	°C	

AVAILABLE PACK SIZE, ARTICLE

20L ART. 85022 60L ART. 85023

200L ART. 85024

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.