

## BIZOL Technology

### OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



**BIZOL Technology 5W-30 C2** is a modern HC motor oil for all season use in petrol engines of passenger cars. Specially developed for vehicles of Japanese and Korean car manufacturers. Meets the latest requirements for piston clearness and engine sludge protection. Provides the better durability of catalyst and turbocharger.

#### BENEFITS

- excellent wear protection
- increased clearness of the engine parts
- increased oil change intervals are possible

#### SPECIFICATIONS

ACEA C2

Ilac GF 4 / GF 5

API SN / CF

#### APPROVALS /

#### RECOMMENDATIONS

**DAIHATSU**

Daihatsu

**FIAT**

9.55535 S1

**HONDA**

Honda

**HYUNDAI**

Hyundai

**KIA**

KIA

**LEXUS**

Lexus

**MAZDA**

Mazda

**MITSUBISHI**

Mitsubishi

**NISSAN**

Nissan

**PEUGEOT/CITROËN**

PSA B71 2290

**RENAULT**

RN 0700

**SUBARU**

Subaru

**SUZUKI**

Suzuki

**TOYOTA**

Toyota

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	224 °C	DIN ISO 2592
Viscosity at 100°C	9,7 mm²/s	DIN 51 562
Density at 15 °C	857 kg/m³	DIN 51 757
Viscosity class SAE	5W-30	
TBN (Total base number)	8,2 mg KOH/g	
Viscosity at 40°C	53 mm²/s	DIN 51 562
Viscosity index	168	DIN ISO 2909
Pour Point	-36 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	3,1 mPas	
Colour	3	DIN ISO 2049
Sulfate ashes	0,8 %	DIN 51757

## AVAILABLE PACK SIZE, ARTICLE

1L	ART. 81220
4L	ART. 81226

## INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.