

BIZOL Technology

OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



BIZOL Technology 5W-30 507 is a modern high-performance, long-life motor oil with reduced ash content. This oil is universally formulated in compliance with the requirements of VW motors. It is backward compatible to the previous generations of motors under consideration of stipulated oil change intervals. It is suitable for VW vehicles with and without extended oil change intervals, as well as for FSI engines and other types of diesel engines with diesel particulate filter (DPF). Can be applied in diesel engines, such as V10 R5-TDI with pump injector with and without DPF built since 06/2006.

BENEFITS

- developed especially for VW petrol and diesel engines with DPF
- optimal wear protection and extended service life of the engine is possible
- increased oil change intervals are possible

SPECIFICATIONS

ACEA C3

API SM / CF

APPROVALS / RECOMMENDATIONS

AUDI/VW/SEAT/SKODA

VW 504 00 / 507 00

BMW

LL-04

MERCEDES BENZ

MB 229.51

PORSCHE

C30

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	220 °C	DIN ISO 2592
Viscosity at 100°C	11,5 mm²/s	DIN 51 562
Density at 15 °C	853 kg/m³	DIN 51 757
Viscosity class SAE	5W-30	
TBN (Total base number)	6,6 mg KOH/g	DIN ISO 3771
Evaporation loss	8 %	
Viscosity at 40°C	65 mm²/s	DIN 51 562
Viscosity index	172	DIN ISO 2909
Pour Point	-39 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	3,6 mPas	

TECHNICAL DATA

Characteristics	Measurements	Method
Colour	3	DIN ISO 2049
Appearance	slightly brown, clear	
Sulfate ashes	0,7 %	DIN 51575

AVAILABLE PACK
SIZE, ARTICLE

1L	ART. 85820
5L	ART. 85821
20L	ART. 85822
60L	ART. 85823
200L	ART. 85824

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.