

## BIZOL Technology

### OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



BIZOL Technology 5W20 is a modern motor oil based on synthesis technology. The combination of base oils and special additive components results in a motor oil with reduced exhaust emissions and fuel saving properties. BIZOL Technology 5W20 provides a fast lubrication of the engine that significantly reduces wear in the cold start period.

## BENEFITS

- developed especially for most cars of the GM group, where DEXOS 1 is required
- high stability of lubricating film and reliable wear-protection
- unique dispersion properties ensure excellent cleaning properties of all engine components

## SPECIFICATIONS

API SN

Ilvac GF 4 / GF 5

## APPROVALS / RECOMMENDATIONS

**CHRYSLER**

MS-6395

**FORD**

WSS-M2C-945-A / WSS-MSC-946-A

**GENERAL MOTORS/OPEL**

GM 6094 M

DEXOS 1

## TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	230 °C	DIN ISO 2592
Viscosity at 100°C	8,1 mm²/s	DIN 51 562
Viscosity class SAE	5W-20	
TBN (Total base number)	8,7 mg KOH/g	DIN ISO 3771
Evaporation loss	8 %	
Viscosity at 40°C	44 mm²/s	DIN 51 562
Viscosity index	157	DIN ISO 2909
Pour Point	-39 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	2,6 mPas	
Colour	3,5	DIN ISO 2049

TECHNICAL DATA

Characteristics	Measurements	Method
Density at 15 °C	0,854 g/cm³	DIN 51 757
Sulfate ashes	0,9 %	DIN 51575

AVAILABLE PACK  
SIZE, ARTICLE

1L	ART. 84410
5L	ART. 84411

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.