

BIZOL Technology

OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



BIZOL Technology 0W-30 is a highly modern fully synthetic, low-friction motor oil for year-round use. The combination of unique synthetic base oils with an advanced additive technology results in an motor oil with low viscosity and high stability. It reliably prevents deposits, reduces friction losses in the engine, and protects from wear. **BIZOL Technology 0W-30** is recommended for use in petrol and diesel engines including turbochargers and catalytic converters.

BENEFITS

- increased oil change intervals are possible
- excellent engine cleanliness
- optimum wear protection

SPECIFICATIONS

API SN / CF

APPROVALS / RECOMMENDATIONS

AUDI/VW/SEAT/SKODA

VW 502 00 / 505 00

BMW

LL-01

MERCEDES BENZ

MB 229.3 / 229.5

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	225 °C	DIN ISO 2592
Viscosity at 100°C	11,7 mm²/s	DIN 51 562
Viscosity at -30°C	3500 mPas	DIN 51 562
Density at 15 °C	848 kg/m³	DIN 51 757
Viscosity class SAE	0W-30	
ASTM colour number	4	DIN ISO 2049
TBN (Total base number)	9 mg KOH/g	DIN ISO 3771
Evaporation loss	9,6 %	
Viscosity at 40°C	64 mm²/s	DIN 51 562
Ash, sulphate	1,1 g/100g	DIN 51575
Viscosity index	180	DIN ISO 2909

TECHNICAL DATA

Characteristics	Measurements	Method
Pour Point	-39 °C	DIN ISO 3016
High Shear / High Temperature Viscosity	3,5 mPas	

AVAILABLE PACK
SIZE, ARTICLE

1L	ART. 85410
4L	ART. 85416
5L	ART. 85411
20L	ART. 85412
60L	ART. 85413
200L	ART. 85414

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.