BIZOL Technology 0W-20 509



Martin-Buber-Straße 12, 14163 Berlin, Germany

www.bizol.com

2016-10-06

DIZOL Technology

OUTSTANDING FUEL SAVING
FORMULA FOR MODERN CARS

BIZOL Technology 0W-20 509 is a fully synthetic, high performance motor oil meeting the latest standards for VW and Audi engines. This motor oil is effective in optimizing fuel consumption. It has excellent wear protection properties increasing the longevity of the engine. Attention: **BIZOL Technology 0W-20 509** is not backward compatible and cannot be used in vehicles that require the VW norm 504 00 / 507 00.

BENEFITS

- meets the latest VW and Audi standards (VW 508 00 / 509.00)
- excellent fuel saving properties
- excellent wear protection

APPROVALS / RECOMMENDATIONS

AUDI/VW/SEAT/SKODA

VW 508 00 / 509 00

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	>200 °C	DIN ISO 2592
Viscosity at 100°C	8,2 mm ² /s	DIN 51 562
Viscosity class SAE	0W-20	
TBN (Total base number)	8,2 mg KOH/g	DIN ISO 3771
Viscosity at 40°C	40 mm²/s	DIN 51 562
Viscosity index	184	DIN ISO 2909
Pour Point	-48 °C	DIN ISO 3016
Density at 15 °C	0,830 g/cm³	DIN 51 757

AVAILABLE PACK SIZE, ARTICLE

1L

ART. 81090

5L ART. 81091

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

1/1