

BIZOL Technology

OUTSTANDING FUEL SAVING FORMULA FOR MODERN CARS



Bizol Technology 0W-20 is a synthetic motor oil effective especially for downsized modern engines which need to be very fuel efficient. It is suitable for engines with exhaust-gas-turbocharger and charge-air coolers. The combination of base oils and additives result in a motor oil which provides an effective wear protection at high and low external temperatures.

BENEFITS

- Increases fuel efficiency
- Can be used with fuels containing Ethanol E85
- Provides effective engine protection

SPECIFICATIONS

API CF / SN

Ilsac GF 5 / GF 4

APPROVALS / RECOMMENDATIONS

BMW

LL 14 FE+

CHRYSLER

MS-6395

GENERAL MOTORS/OPEL

GM 6094 M

HONDA

Honda

Land Rover

Range Rover STJLR. 51.5122

TOYOTA

Toyota

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	<220 °C	DIN ISO 2592
Viscosity at 100°C	8,5 mm²/s	DIN 51 562
Viscosity class SAE	0W-20	
TBN (Total base number)	7,9 mg KOH/g	
Viscosity at 40°C	45,2 mm²/s	DIN 51 562
Viscosity index	168	DIN ISO 2909
Pour Point	-48 °C	DIN ISO 3016
Colour	3,0	DIN ISO 2049
Density at 15 °C	0,84 g/cm³	DIN 51 757

AVAILABLE PACK SIZE, ARTICLE

5 L

ART. 85811

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.