

CEPSA GENUINE 15W40

Description



A multigrade oil formulated from a combination of select first refining, mineral bases, together with high performance additives. The product is suitable for most existing passenger cars (including turbocharged).

Applications

- High-performance low-consumption oil, which is very suitable for all types of diesel salon cars, including TDI engines (direct injection, turbocharged and EGR, etc.).
- Because of its API SL and ACEA A3 quality, it is considered very suitable for multi-valve, turbocharged engines and specially those classed as GTI.
- For high performance engines in all types of saloon cars which require a long duration oil under both normal and demanding driving conditions.
- Where it requires a Sae 15W40 oil with MB-229.1 and/or VW 501.0/505.00 quality level.
- Recommended for conditions of severe use: dense traffic and high speed, etc.

Performance

- Better low temperature and cold starting fluidity than SAE grades 20W-50 and 20W-40.
- Its high detergent-dispersant capability provides excellent engine cleanliness and its balanced TBN reduces the effects of corrosive acids produced by combustion.
- Excellent engine protection, lengthening its life.
- Its "long duration" quality increases the change interval of ACEA A3/B3 habitual mineral oils.
- Helps decrease exhaust emissions and, thanks to its low phosphorous content, extends the life of catalytic converters.

Specifications

• ACEA A3/B4-12 • API SL /CF

CHARACTERISTICS	UNITS	MÉTHOD	CEPSA GENUINE 15W40
SAE Grade	-	-	15W40
Density at 15°C	g/ml	ASTM D 4052	0,8846
Viscosity at 100°C	cSt	ASTM D 445	14,3
Viscosity at 40°C	cSt	ASTM D 445	105
Viscosity Index	-	ASTM D 2270	139
CCS Viscosity at -30°C	сР	ASTM D 5293	5800
Freezing Point	٥C	ASTM D 97	-30
Flash Point (COC)	٥C	ASTM D 92	>200
Base number, TBN	mg KOH/g	ASTM D 2896	11
Sulphated Ash	% (m/m)	ASTM D 874	1,2
HTHS Viscosity at 150°C	сР	ASTM D 4683	3,9

Tvpical Characteristics

Balth & Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.