

CVL TURBO

Page: 1

Compilation date: 30/11/2007

Revision date: 16/06/2017

Revision No: 1b

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CVL TURBO

Product code: 5792

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Octane booster, valve seat lubricant and combustion enhancer.

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd

Hillside Oilworks
Rastrick Common

Brighouse

West Yorkshire

HD6 3DP

United Kingdom

Tel: +44 (0)1484 713201

Fax: +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; STOT SE 3: H336; Aquatic Chronic 2: H411; Carc. 2: H351; Asp. Tox.

1: H304; Skin Irrit. 2: H315; Repr. 1B: H360FD

Most important adverse effects: May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious

eye damage. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility. May damage the unborn child. Toxic to aquatic life with long lasting

effects.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

CVL TURBO

Page: 2

H315: Causes skin irritation.

H318: Causes serious eye damage.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

H360FD: May damage fertility. May damage the unborn child.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice/attention.

P331: Do NOT induce vomiting.

P501: Dispose of contents/container to disposal should be in accordance with local,

state or national legislation.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE - REACH registered number(s): 01-2119463588-24

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-284-0	-	-	Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411	50-70%

NAPHTHA (PETROLEUM), HEAVY AROMATIC - REACH registered number(s): 01-2119463588-24-XXXX

265-198-5	-	-	Aquatic Chronic 2: H411; Asp. Tox. 1:	10-30%
			H304	

CVL TURBO

Page: 3

POTASSIUM 1.2-BIS(2-ETHYLHEXYLOXYCARBONYL)-ETHANESULPHONATE

231-308-5	7491-09-0	- Skin Irrit. 2: H315; Eye Dam. 1	: H318 1-10%
NAPHTHALEI	NE		
202-049-5	91-20-3	- Carc. 2: H351; Acute Tox. 4: H Aquatic Chronic 1: H410; Aqua 1: H400	
FERROCENE	- REACH registe	red number(s): 01-2119978280-34-XXXX	
203-039-3	102-54-5	- Flam. Sol. 1: H228; Acute Tox. H302+332; Repr. 1B: H360FD RE 2: H373; Aquatic Chronic 1 Aquatic Acute 1: H400	; STOT
1,2,4-TRIMET	HYLBENZENE		
202-436-9	95-63-6	- Flam. Liq. 3: H226; Acute Tox. Eye Irrit. 2: H319; STOT SE 3: Skin Irrit. 2: H315; Aquatic Chr H411	H335;
1,3,5-TRIMET	HYLBENZENE)N	MESITYLENE)	,
203-604-4	108-67-8	- Flam. Liq. 3: H226; Asp. Tox. 1 Skin Irrit. 2: H315; Eye Irrit. 2: I STOT SE 3: H335; Aquatic Ch	H319;

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be coughing and a sore throat.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises. Show this safety data

sheet to the doctor in attendance.

Section 5: Fire-fighting measures

CVL TURBO

Page: 4

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

CVL TURBO

Page: 5

Workplace exposure limits:

Respirable dust

Sta	te	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
Uk	<	220mg/m3	441mg/m3	-	-

Hazardous ingredients:

1,2,4-TRIMETHYLBENZENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	125 mg/m3	-	-	•

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless
Odour: Aromatic

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Immiscible in water.

Also soluble in: Most organic solvents.

Viscosity: No data available.

Kinematic viscosity: 0.8-2 cSt

Boiling point/range°C: 160 - 230 **Melting point/range°C:** No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: >62 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.910 **pH:** No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

CVL TURBO

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Hot surfaces. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

NAPHTHALENE

ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	490	mg/kg
SKN	RAT	LD50	>2500	mg/kg

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation OPT		Hazardous: calculated
Carcinogenicity		Hazardous: calculated
Reproductive toxicity		Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

CVL TURBO

Page: 7

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be coughing and a sore throat.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Contains: naphthalene, ferrocene)

14.3. Transport hazard class(es)

Transport class: 9

CVL TURBO

Page: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H228: Flammable solid.

H302: Harmful if swallowed.

H302+332: Harmful if swallowed or if inhaled.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

H360FD: May damage fertility. May damage the unborn child.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that

no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

CVL TURBO

Page: 9

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.