

TITAN RACE SYNCHRO 75W-90

High quality manual transmission oil for arduous conditions

Description

TITAN RACE SYNCHRO 75W-90 is a heavy duty manual transmission fluid for use in manual transmissions including synchromesh types fitted to many high performance cars.

TITAN RACE SYNCHRO 75W-90 utilises the latest and most advanced additive technology along with selected fully synthetic base stocks to provide outstanding thermal stability and excellent corrosion protection. The modern additive technology also provides outstanding load carrying and antiwear performance and will protect driveline components under the most demanding applications and operating conditions.

Application

TITAN RACE SYNCHRO 75W-90 is designed for use in manual transmissions operating under arduous and high speed applications where an oil of this viscosity and performance level is specified TITAN RACE SYNCHRO 75W-90 is especially recommended for road going track cars.

Advantages

- Provides optimum lubrication and protection over a very wide operating temperature range, eliminating low temperature gear selection problems, as well as providing excellent protection to highly stressed components at high operating temperatures
- Very good synchromesh performance ensures easy gear shifts under heavy loads and high speed acceleration
- Excellent rationalisation grade, TITAN RACE SYNCHRO 75W-90 can be safely recommended where SAE 90, 85W-90 or 80W-90 grades are specified
- Outstanding load carrying capacity and antiwear performance can help extend component life
- Gives true “stay in grade” performance for the entire drain period
- Allows optimum power transfer across the entire temperature range

Specifications

- I SAE 75W-90
- API GL-4

FUCHS Recommendation

- Manual transmissions
- Synchromesh gearboxes

Product Information



Further Information

CHARACTERISTICS: TITAN RACE SYNCHRO 75W-90

Kinematic Viscosity at 100°C	IP71	14.5mm ² /s
Kinematic Viscosity at 40°C	IP71	96.5 mm ² /s
Viscosity Index (VI)	IP226	158
Specific Gravity at 15°C	IP160	0.849
Flash Point (Closed Cup)	IP34	223°C
Pour point	IP15	-51°C

Reviewed 14/04/2020 AB

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.