



# High Performance Lubricants



## Technical Data

### Synthesis F 5W-30

Synthesis F 5W-30 is a fully synthetic lubricant produced from state of the art additives in combination with severely hydrotreated hydrocarbon base stocks to provide an ultra modern lubricant.

Synthesis F 5W-30 is specially formulated to exceed Ford's demanding fuel economy targets and is intended primarily for use where Ford WSS-M2C913-D is recommended. It is also suitable for use where M2C 913-A, M2C 913-B & M2C 913-C are recommended and in other vehicles where the viscosity and quality claims are appropriate.

### Features

Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably  
Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions

Enhanced low temperature capabilities for outstanding cold weather starting

Recommended for use in petrol, naturally aspirated and turbo charged diesel engines

### Performance Specifications / Approvals

ACEA A1/B1, A5/B5

API SN/CF

FORD M2C 913-D

FORD M2C 913-C, M2C 913-B, M2C 913-A

RENAULT RN0700

### Typical Physical Characteristics

Viscosity Grade	SAE 5W-30
Density @ 15C	0.852
Viscosity @ 40C	57.0 cSt
Viscosity @ 100C	10.4 cSt
Viscosity Index	174
Appearance	Clear Amber Liquid
Product Code	01570

Rev:F/14