



High Performance Lubricants



Technical Data

Strata SS 5W-30 Semi-Synthetic Engine Oil

Strata SS 5W-30 is a lubricant produced from state of the art synthetic additives in combination with severely hydrotreated hydrocarbon and mineral base stocks to provide an ultra modern lubricant.

Strata SS 5W-30 can be used in a variety of petrol and diesel cars, light trucks and vans. Strata SS 5W-30 is intended primarily for use where Ford WSS-M2C913-A and M2C913-B are recommended but is also suitable for use in other vehicles where the viscosity and quality claims are appropriate.

Features

Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably
Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions
Enhanced low temperature capabilities for outstanding cold weather starting
Recommended for use in petrol, naturally aspirated and turbo charged diesel engines

Performance Specifications / Approvals

ACEA A1/B1, A5/B5
API SL/CF
FORD WSS M2C 913A/B

Typical Physical Characteristics

Viscosity Grade	SAE 5W-30
Density @ 15C	0.854
Viscosity @ 40C	54.0 cSt
Viscosity @ 100C	10.1 cSt
Viscosity Index	175
Appearance	Clear Amber Liquid
Product Code	01590

Rev:F/14