



TITAN RACE PRO S 10W-60

Ester synthetic 4-Stroke oil for high performance engines

Description

TITAN RACE PRO S 10W-60 is a race proven engine oil with a high synthetic content. Utilising advanced wear reducing chemistry, ester synthetic base materials and technology derived from aircraft turbojet engine lubrication, TITAN RACE PRO S 10W-60 exhibits load-carrying and film strength properties considerably in excess of those achieved with conventional mineral or synthesised hydrocarbon lubrications (PAOs).

Application

TITAN RACE PRO S 10W-60 provides outstanding protection for highly stressed engines. It is recommended for use in all high output engines where SH or SJ lubricants are specified. TITAN RACE PRO S 10W-60 may be used to advantage in many modified engines in competition applications.

The advanced wear reducing chemistry, ester synthetic base materials and technology derived from aircraft turbojet lubrication makes TITAN RACE PRO S 10W-60 ideally suited for use in highly stressed turbo charged competition units.

TITAN RACE PRO S 10W-60 gives excellent performance in competition cars which use motorcycle-type combined engine/transmission lubrication. Very high film strength and stable multigrade characteristics give optimum protection and superior gear change characteristics.

All high performance power units running on lead-free, low-lead or racing gasolines benefit from the extra protection of TITAN RACE PRO S 10W-60. Also for use in applications where excessive fuel dilution has been encountered.

Advantages/Benefits

- High detergency ensures exceptional engine cleanliness
- Test bed and extensive racing experience show significant increases in power output
- High film strength reduces wear and friction, ensuring reliability and long component life
- Unique formula releases entrained air quickly, minimising risk of oil starvation
- Advanced surface chemistry provides vital protection to pistons and bores, cam lobes and bearings
- Excellent shear stability for 'stay-in-grade' performance
- Improved high temperature deposit control and oxidation stability

FUCHS Recommendations

Recommended for use where the following specifications are quoted

- API SL, SJ & SH



March 2015 GDUK Page 1 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products



CHARACTERISTICS: TITAN RACE PRO S 10W-60

Kinematic Viscosity at 100°C	IP71	23.04 mm ² /s
Kinematic Viscosity at 40°C	IP71	150 mm ² /s
Viscosity Index (VI)	IP226	184
Cold Crank Viscosity at -20°C		6100 cP
SAE Rating		10W-60
Pour point	IP15	-39°C
Colour		Red
Specific Gravity at 15°C	IP160	0.860
Flash Point (Closed Cup)	IP34	200°C



March 2015 GDUK Page 2 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products