



PLATINUM PRO V 5W-30

Quality class: ACEA: C3
Viscosity grad: SAE: 5W-30

GENERAL FEATURES:

Platinum PRO is the latest generation of engine oil for professional applications with the revolutionary SMART Formula and double filtration system. Platinum PRO complies with or exceeds the latest requirements of car manufacturers. Double filtration guarantees the highest quality and exceptional purity of the oil. SMART Formula means confidence and reliability of the engine in all circumstances: · exceptional engine protection under all kinds of conditions; · lower costs of operation due to reduced fuel consumption; · reduction in the emission of environmentally harmful substances.

APPLICATION:

Platinum PRO V 5W-30 has been designed for all-year lubrication of modern car and van petrol engines with catalytic converters and Diesel engines with and without turbocharger with exhaust gas reduction systems, such as: Diesel particulate filter and three-way catalytic converter. The oil complies with the latest Volkswagen requirements VW 504.00/507.00 but can also be used with engines with older VW specifications. Apart from the makes of Volkswagen: Audi, Seat i Skoda, the oil is great for passenger and off-road cars by other manufacturers. It is recommended for vehicles compliant with the Euro 6 standard.

STANDARDS, APPROVALS. SPECIFICATION:

Approvals:
VW 504.00/ 507.00
MB-Approval 229.51
BMW Longlife-04
Porsche C30



Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	5W-30
kinematic viscosity at 100°C	mm ² /s	12,0
viscosity index	-	170
structural viscosity CCS at -30°C	mPa*s	6060
TBN	Mg KOH/g	6,4
sulphated ash	%	0,74

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

