



## PLATINUM PRO XFI 5W-30

**Quality class:** API: SN/SM/CF

ACEA: C2

**Viscosity grad:** SAE: 5W-30

### GENERAL FEATURES:

Platinum PRO is the latest generation of professional engine oil with the revolutionary SMART Formula and double filtration system. Platinum PRO complies with or exceeds the latest requirements of car manufacturers. Double filtration guarantees the highest quality and exceptional purity of the oil. SMART Formula means confidence and reliability of the engine in all circumstances:

- exceptional engine protection under all kinds of conditions;
- lower costs of operation due to reduced fuel consumption;
- reduction in the emission of environmentally harmful substances.

### APPLICATION:

Platinum PRO XFI 5W-30 has been designed with drivers preferring PSA-Citroen, Peugeot and Renault and Fiat concerns' cars in mind. It is recommended for cars and vans with Diesel or petrol engines with and without turbocharger. It may be used in environment friendly vehicles with exhaust gas reduction systems, such as: Diesel particulate filter and three-way catalytic converter. Additionally, it extends their lifetime. Corresponds to the quality level of the ILSAC GF-4 standard. It is recommended for vehicles compliant with the Euro 6 standard.

### STANDARDS, APPROVALS. SPECIFICATION:

Approvals:  
Renault 0700

Meets requirements of:  
PSA B71 2290 / Citroen, Peugeot,  
Fiat 9.55535-S1



## Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	5W-30
kinematic viscosity at 100°C	mm <sup>2</sup> /s	10,2
viscosity index	-	160
structural viscosity CCS at -30°C	mPa*s	5380
TBN	Mg KOH/g	7,9
sulphated ash	%	0,75

**NOTE:**  
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

