



Motorsport 5W-50

Fully Synthetic

Recommended by Comma for applications requiring:

Suitable for replacing ACEA A3/B3; API SL CF, SAE 5W-40, 10W-40 & 15W-40 oils in Motorsport applications.

Product Features:

- Fully synthetic, high performance 5W-50 oil, for motorsport and track day use.
- Track tested to give high performance under extreme race conditions.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Typical Inspection Data:

Density @ 20°C	0.852
Viscosity @ 100°C	17.0 cSt
Viscosity @ 40°C	103 cSt
Viscosity Index	175
Viscosity CCS @ -30°C	5500 cP
T.B.N.	6.5 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.11%
Calcium	0.25%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

10-10-2014