



Typical Inspection Data:

Density @ 20 °C	0.848 g/cm ³
Viscosity @ 100 °C	9.9 cSt
Viscosity @ 40 °C	55 cSt
Viscosity Index	166
Viscosity CCS @ -30 °C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

Xtech 5W-30

Fully Synthetic

Official Approvals:

Acknowledged by Ford to meet the requirements of WSS-M2C913-D

Recommended by Comma for applications requiring:

FORD WSS-M2C913-C, WSS-M2C913-B, WSS-M2C913-A;
Jaguar Land Rover STJLR 03.5003;
ACEA A5/B5; API SL CF

Product Features:

- Fully synthetic, high performance 5W-30 oil, for Ford DuraTec, DuraTorq and Zetec Vehicles, offering the fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

12-09-2017