



## Typical Inspection Data:

Density @ 20 °C	0.844 g/cm <sup>3</sup>
Viscosity @ 100 °C	8.4 cSt
Viscosity @ 40 °C	42 cSt
Viscosity Index	170
Viscosity CCS @ -35 °C	5000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.16%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-30 °C

## Pro-NRG 0W-20

Fully Synthetic

**Recommended by Comma for applications requiring:**

API SN; ILSAC GF-5; dexos 1:2015; Chrysler MS 6395; GM6094M & GM4718M

## Product Features:

- Fully synthetic, high performance 0W-20 oil for modern petrol vehicles and most petrol-electric hybrids.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

## Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

## Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

12-09-2017