



## Pro-VLL 0W-30

Fully Synthetic

**Recommended by Comma for applications requiring:**

VW 503 00,  
VW 506 00,  
VW 506 01

### Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for diesel PD Volkswagen engines running on LongLife Service regime.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com).

### Typical Inspection Data:

Density @ 20 °C	0.853
Viscosity @ 100 °C	9.5 cSt
Viscosity @ 40 °C	53 cSt
Viscosity Index	165
Viscosity CCS @ -35 °C	5900 cP
T.B.N.	9.7 mg KOH/g
Sulphated Ash Mass	1.2%
Zinc	0.14%
Calcium	0.28%
Phosphorus	0.12%
Colour	Amber
Flash Point	>200°C
Pour Point	-42°C

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

28-12-2016