

PETRONAS SYNTIUM 3000 SAE 5W-40

Specially Engineered Ultimate Performance Engine Oil Exceeds the Latest API SM Specifications

Petronas Syntium 3000 SAE 5W-40 is the next generation fully synthetic ultimate performance multigrade engine oil specially engineered to provide the ultimate engine protection and performance for current and future generation high performance engines running under the most extreme, most demanding driving conditions. It is exclusively formulated with premium synthetic base fluids and high performance additives system that provide exceptional thermal and oxidation stability to ensure very minimum oil thickening at very high operating temperature, excellent deposits control and minimized engine wear and tear.

With extensive field, racetrack and testing experiences over many years, Petronas Syntium has been developed with the F1 technology in mind to deliver the ultimate performance lubricant that provide complete engine protections especially for engines operating under the most extreme, most demanding operating conditions throughout today's long drain interval.

Applications

Recommended for use in all types of passenger cars especially the latest model high performance cars fitted with emission control devices, fuel injections, multi-valves, turbochargers or superchargers operating under the most extreme conditions. Also suitable for engines requiring API SL, SJ, SH, SG or lower performance levels.

Customer Benefits

- Ultimate engine protection at all driving conditions
- Prolong engine life
- Exceptional engine cleanliness - protects against engine sludge and varnish deposits
- Resists viscosity and thermal breakdown even in the most extreme service
- Very high shear stability – stay in grade
- Superior cold engine starting – minimize friction and wear at start-up

Customer Advice

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.

Product Typicals

Characteristics	SAE 5W-40
Density @ 15 °C, kg/l	0.8520
Pour Point, °C	-42
Flash Point, °C	220
Kinematic Viscosity, cSt	
@ 40 °C	79.2
@ 100 °C	13.6
Viscosity Index	177
Cold Cranking Visc, cP	
@ - 30 °C	4,884
Sulphated Ash, %wt	0.95
TBN, mg KOH/g	9
ASTM Colour	2.5

Specifications

- API SM/CF
- ACEA A3/B3/B4
- MB p229.5
- BMW LL-01
- VW 502/505
- Porsche A40