



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-210. MITASU EURO PAO LL III OIL 5W-30 100% Synthetic



4L



6L



20L



200L

MITASU EURO PAO LL III OIL 5W-30 100% Synthetic is a fully synthetic energy saving motor oil of low SAPS grade. It meets the ACEA C3-10 requirements and other European OEM standards, such as VW 504.00/507.00, BMW Longlife-04, MB Approval 229.51 and PORSCHE C30. It is developed from a base oil group IV (PAO), combined with a modern system of enhancing additives with low levels of phosphorus and sulfur.

APPLICATION

MITASU EURO PAO LL III OIL 5W-30 100% Synthetic is especially developed in accordance to modern requirements to oils for engines with extended intervals of vehicle maintenance of following automotive manufactures: Volkswagen Group (VW, Audi, Skoda, Seat), Mercedes-Benz, BMW, Porsche. It meets the EURO IV standard, including vehicles fitted with diesel particulate filters (DPF) and/or three-way catalysts. It extends the life of diesel particulate filters and catalysts due to low levels of sulfated ash, phosphorus and sulfur. The product is suitable for all motors with requirements for ACEA C3 oils.

SPECIFICATIONS / APPROVALS

- ACEA C3-10
- API SN/CF
- VW 504.00/507.00
- BMW Longlife-04
- MB Approval 229.51
- PORSCHE C30



APPLICATION BENEFITS

Fully synthetic diesel oil MITASU EURO PAO LL III OIL 5W-30 100% Synthetic provides:

- The level of quality specified by Original Equipment Manufacturers (OEM)
- Fuel economy
- Reduced engine warm-up time
- Significant extension of drain interval
- Extended life of diesel particulate filters and catalytic converters

The newest technologies MITASU OIL CORPORATION, Japan allow MITASU EURO PAO LL III OIL 5W-30 100% Synthetic meets requirements of the following manufactures, as: VOLKSWAGEN, AUDI, SKODA, SEAT, PORSCHE, MERCEDES-BENZ, BMW and many other.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	5W-30
Density at 15°C	ASTM D-4052	0,8560
Flash point, °C	ASTM D-92	225
TBN (mg KOH/g)	ASTM D-2896	5,80
Pour point, °C	ASTM D-97	-42
Colour	ASTM D-1500	2,5
Viscosity index	ASTM D-2270	170
Kinematic viscosity at 40°C (cSt)	ASTM D-445	67,90
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,80

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2016 Mitsuru Oil Corporation, Japan.