



DATA SHEET NO: 7625

PRODUCT NAME/VISCOSITIES:

TRIDENT 5w40

DESCRIPTION:

Trident 5w40 is a fully synthetic engine oil formulated to meet the latest requirements for engines operating under severe conditions.

APPLICATION:

Recommended for use in current and late model petrol and diesel cars where this type of advanced engine oil is called for by the manufacturer, especially modern high performance vehicles.

Also suitable for turbo charged engines.

USER BENEFITS:

- Full protection provided even under extreme operating conditions including long service intervals. Its use is essential in modern cars to enable fuel economy to be maximised.
- Provides easy starting and quick circulation of the oil even under very cold conditions.
- Full synthetic properties improve fuel economy, lower maintenance costs and maximize the drain interval.

PERFORMANCE PROFILE:

- ACEA A3 / B3, A3 / B4
- API SL, CF
- Meets the requirements of MB 229.1, MB 229.5, VW 502 00, 505 00, BMW Longlife-01, Porsche A40, Renault RN0710

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 5w40
Specific Gravity @ 15°C 0.857
Kinematic Viscosity @ 100°C 12.79cSt
Kinematic Viscosity @ 40°C 77.7cSt
Viscosity Index 165
Pour point °C <-30
Flashpoint °C >200

Cold Crank Viscosity @ -30°C 6,600cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 7625 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited Brighouse West Yorkshire HD6 3DP **Tel** +44 (0)1484 713201 **Fax** +44 (0)1484 721263

Email enquiries@millersoils.co.uk

www.millersoils.co.uk



