



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

Trident



AUTOMOTIVE



PRODUCT NAME/VISCOSITIES:

TRIDENT 10w40

DATA SHEET NO: 5991

DESCRIPTION:

A high quality semi synthetic engine oil for cars and light vans.

APPLICATION:

For use in more modern petrol and diesel vehicles where advantage can be taken of lighter lower viscosity oils for additional power and fuel economy. Suitable for turbo charged engines.

USER BENEFITS:

- Trident is a SAE 10w40 viscosity grade product which is the preferred grade for many modern engines
- It is an ideal lubricant for the modern multi-valve engine designs with hydraulic valve lifters
- Trident 10w40 provides excellent fuel economy whilst maintaining high levels of engine protection

PERFORMANCE PROFILE:

- ACEA A3 / B3, A3 / B4
- API SL, CF
- MTF-94 Manual transmission specification
- Meets the requirements of MB 229.1, VW 502 00, 505 00, Renault RN0700

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	10w40
Specific Gravity @ 15°C	0.872
Kinematic Viscosity @ 100°C	14.1cSt
Kinematic Viscosity @ 40°C	96.7cSt
Viscosity Index	149
Pour point °C	<-42
Flashpoint °C	>200
Cold Crank Viscosity @ -25°C	7,000cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 5991 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

